

BONDERITE L-GP 6041 CR

SOLVENT BASED CORROSION INHIBITOR

(KNOWN AS P3 PREVOX 6041CR)

Issued
8/14/2014

PRODUCT TECHNOLOGY

BONDERITE L-GP 6041 CR (known as P3 Prevox 6041CR) is a solvent-based corrosion inhibitor designed for extended corrosion protection on ferrous and galvanized alloys. Its unique composition provides a durable product for today's heavy-duty corrosion protecting needs.

TYPICAL PROPERTIES

Property	Concentrate
Appearance	Clear Dark Brown
Film Type	Non-Tacky

OPERATING SUMMARY

BONDERITE L-GP 6041 CR is generally used as received for most operations. BONDERITE L-GP 6041 CR provides extended indoor protection up to 6-12 months. Results are typical with normal production practices and do not constitute a specification. Consult your HENKEL Representative for more specific recommendations on your particular operation and conditions.

APPLICATION TECHNOLOGIES

Dipping, spraying, hand application and other techniques are suitable for application to the metal surface. consult your HENKEL Representative for more specific recommendations on your particular operation and conditions.

PRODUCT REMOVAL

BONDERITE L-GP 6041 CR can be removed by most alkaline systems. Consult your HENKEL sales representative for more specific cleaning product recommendations.

STORAGE REQUIREMENTS

BONDERITE L-GP 6041 CR should be protected from freezing. Store BONDERITE L-GP 6041 CR above 40°F and below 100°F for best results.



BONDERITE L-GP 6041 CR

SOLVENT BASED CORROSION INHIBITOR

(KNOWN AS P3 PREVOX 6041CR)

WASTE DISPOSAL

Please follow all applicable Federal, state and local regulations regarding proper disposal of this product.

For more information about Henkel Surface Technologies products and services, please contact your local HENKEL representative or call our Technical Help Desk at (248)-577-2058.

Henkel Corporation | 32100 Stephenson Highway | Madison Heights, MI 48071
PHONE: (248) 583-9300 | FAX: (248) 583-2976 | www.henkelna.com/

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

