

**BONDERITE L-AD S**  
**LUBRICANT ADDITIVE**  
(KNOWN AS P3 MULTAN S)

Issued 6/3/2013

PRODUCT SUMMARY AT A GLANCE	
Product type	Synthetic
Metal type	Steel, Cast Iron, Aluminum, Copper, Brass, Bronze
Application	System Cleaner

**Typical Properties:**

Property	Concentrate	Dilution
Appearance	Yellow fluid	
pH		7.0 at 1%

**Operating Summary:**

BONDERITE L-AD S (known as P3 MULTAN S) is designed to be used at a 1% concentration in the coolant. Consult your HST Representative for more specific recommendations on your particular operation and conditions.

**Storage requirements:**

BONDERITE L-AD S (known as P3 MULTAN S) should be protected from freezing. Store BONDERITE L-AD S (known as P3 MULTAN S) above 40°F and below 100°F for best results.

**Integrated Equipment Solutions**

Henkel offers a full range of equipment solutions, including refractometers, proportioners, oil coalescers, automated control systems, titration chemicals and bulk tanks.

**Health, Environment & Safety**

Routine maintenance and monitoring should be completed to ensure that the systems are operating as designed. Please follow all applicable Federal, state and local regulations regarding proper disposal of this product. Please consult the Material Safety Data Sheet for more detail on the safe handling of this product.



**BONDERITE L-AD S**  
**LUBRICANT ADDITIVE**  
(KNOWN AS P3 MULTAN S)**Additional Information**

For more detail on this product, or Henkel's capabilities, contact your local account representative or the phone number below.

Henkel Corporation | 32100 Stephenson Highway | Madison Heights, MI 48071  
PHONE: (248) 583-9300 | FAX: (248) 583-2976 | [www.henkelna.com/](http://www.henkelna.com/)

**Trademark usage**

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

