

Revision Number: 004.3 Issue date: 11/17/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Region:

BONDERITE L-FM PL 101 FORMING IDH number: **Product name:** 594526

LUBRICANT ACHESON known as

MULTAN PL 101

Product type: Lubricant

Restriction of Use: None identified Company address:

Henkel Corporation

One Henkel Way Rocky Hill, Connecticut 06067

Contact information: Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

United States

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW		
WARNING:	CAUSES SKIN IRRITATION.	
	CAUSES SERIOUS EYE IRRITATION.	

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A

PICTOGRAM(S)



Precautionary Statements

Prevention: Wash thoroughly after handling. Wear eye and face protection. Wear protective gloves. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for Response:

several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take

off contaminated clothing.

Storage: Not prescribed Disposal: Not prescribed

2 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*

Product name: BONDERITE L-FM PL 101 FORMING LUBRICANT ACHESON known as MULTAN PL IDH number: 594526

Petroleum distillates, hydrotreated, light naphthenic	Proprietary	60 - 100
Oil soluble magnesium sulfonate	Proprietary	10 - 30

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: If mist or vapor of this product is inhaled, remove person immediately to fresh

air. Seek medical attention if symptoms develop or persist.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). If

symptoms develop and persist, get medical attention.

Eye contact: In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

Ingestion: If material is ingested, immediately contact a physician or poison control

center. DO NOT induce vomiting unless directed to do so by medical

personnel.

Symptoms: See Section 11.

Notes to physician: This material, if aspirated into the lungs, may cause chemical pneumonitis;

treat the affected person appropriately.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: This product is combustible at high temperatures.

Hazardous combustion products: Oxides of carbon.

IDH number: 594526

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear suitable protective

clothing, gloves and eye/face protection.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of

this product. For industrial use only. Use good hygiene practices when handling this material, including changing and laundering work clothes after use. Discard contaminated shoes and leather goods. Keep away from heat,

spark and flame.

Storage: Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials. Do not pressurize, cut, heat or weld containers. Empty product containers may contain product residue. Do not reuse empty

containers.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Petroleum distillates, hydrotreated, light naphthenic	5 mg/m3 TWA Inhalable fraction.	500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None
Oil soluble magnesium sulfonate	None	None	None	None

Engineering controls: Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection: Respirators should be selected by and used under the direction of a trained

health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2-1992). A written respiratory protection program, including provisions for medical certification, training, fit testing, exposure assessments, maintenance, inspection, cleaning, and convenient, sanitary storage must be implemented. If concentrations are below the TLV and/or PEL, a NIOSH approved disposable dust/mist respirator may be used for personal comfort. For concentrations above the TLV and/or PEL but less than 10 times these limits, a NIOSH approved half-facepiece respirator equipped with dust-mist cartridges may be used. For concentrations greater than 10 times these limits, consult the NIOSH respirator decision logic found in Publication No. 87-116 or

ANSI Z88.2-1992.

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible).

Skin protection: Acceptable materials for gloves include: polyvinyl chloride; neoprene; nitrile;

polyvinyl alcohol; viton. Gloves should be tested to determine suitability for

prolonged contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:AmberOdor:Mineral oilOdor threshold:Not available.pH:Not applicableVapor pressure:Not determinedBoiling point/range:250 °F (121.1 °C) None

Melting point/ range:

Not available.

Specific gravity: 0.912 - 0.915 at 16 °C (60.8 °F)

Vapor density: Not determined

Flash point: 138 °C (280.4 °F) HST-US 027F

Flammable/Explosive limits - lower: Not available.

IDH number: 594526 Product name: BONDERITE L-FM PL 101 FORMING LUBRICANT ACHESON known as MULTAN PL

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

Not available.

Not available.

Not available.

VOC content: 34.5 % EPA Method 24

Viscosity:Not available.Decomposition temperature:Not available.

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: None under normal processing.

Hazardous decomposition

products:

IDH number: 594526

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons.

Incompatible materials: Strong oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Heat, flames, sparks and other sources of ignition.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system.

Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.

Skin contact: Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

Eye contact: This product may cause irritation to the eyes.

Ingestion: Ingestion of this product may cause nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Petroleum distillates, hydrotreated, light naphthenic	None	Irritant
Oil soluble magnesium sulfonate	None	No Data

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Petroleum distillates, hydrotreated, light naphthenic	No	No	No
Oil soluble magnesium sulfonate	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: No data available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number: Wastes must be tested using methods described in 40 CFR Part 261 to

determine if it meets applicable definitions of hazardous wastes. Material, if discarded, is not expected to be a characteristic hazardous waste under

RCRA.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: None above reporting de minimis

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Jennifer Mckay, Regulatory Affairs Specialist

Issue date: 11/17/2014

IDH number: 594526 Product name: BONDERITE L-FM PL 101 FORMING LUBRICANT ACHESON known as MULTAN PL

Page 5 of 6

101

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.