

Revision Number: 002.2 Issue date: 11/04/2014

## 1. PRODUCT AND COMPANY IDENTIFICATION

**BONDERITE L-CA 193 CASTING Product name: LUBRICANT ACHESON known as** 

**DAG 193** 

Product type: Lubrication Agents for Metal Working

Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

IDH number: 1224571

**United States** Region:

Contact information:

Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW	
DANGER:	CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.	
	MAY CAUSE CANCER.	

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1C
SERIOUS EYE DAMAGE	1
CARCINOGENICITY	1A

### PICTOGRAM(S)



### **Precautionary Statements**

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Do not breathe vapors, mist, or spray. Wash thoroughly after handling. Wear protective gloves, eye protection, and face protection. Use personal protective equipment

as required.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off Response:

immediately all contaminated clothing. IF INHALED: Remove person to fresh air and keep

comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. IF exposed or concerned: Get medical attention. Immediately call a poison control center or physician. Wash contaminated clothing before

reuse.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

4 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

IDH number: 1224571 Product name: BONDERITE L-CA 193 CASTING LUBRICANT ACHESON known as DAG 193

Page 1 of 6

#### See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Ceramic binder	Proprietary	10 - 30
Mica	12001-26-2	5 - 10
Vermiculite	Proprietary	1 - 5
Quartz (SiO2)	14808-60-7	1 - 5

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

# 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Immediately wash skin thoroughly with soap and water. Immediately remove

soiled or soaked clothing. If irritation persists, repeat flushing and get medical attention. Discard any shoes or clothing items that cannot be decontaminated.

Eye contact: Immediately flush eyes with water for at least 15 minutes, while holding

eyelids open. Seek medical attention at once.

Immediate medical treatment necessary. Give one to two glasses of water or

milk. Do not induce vomiting. If vomiting occurs, prevent aspiration by keeping

the patient's head below the knees.

Symptoms: See Section 11.

**Notes to physician:** Treat symptomatically and supportively.

### 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide. In case of fire, keep

containers cool with water spray.

Special firefighting procedures: Fire fighters should wear positive pressure self-contained breathing apparatus

(SCBA).

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat.

Hazardous combustion products: Thermal decomposition can lead to release of irritating gases and vapors.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage. Wear appropriate protective equipment

and clothing during clean-up. Do not allow product to enter sewer or

waterways.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

# 7. HANDLING AND STORAGE

Handling: Use only in well-ventilated areas. Wear suitable protective clothing, safety

glasses and gloves.

Storage: For safe storage, store between 5.0 °C (41°F) and 30.0 °C (86°F)

Keep container closed. Store in a cool, dry, well-ventilated area. Protect from

direct sunlight.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ceramic binder	None	None	None	None
Mica	3 mg/m3 TWA Respirable fraction.			None
Vermiculite	None	None	None	None
Quartz (SiO2)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: If airborne concentrations are above the applicable exposure limits, use

NIOSH approved respiratory protection.

**Eye/face protection:** Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection: Chemical resistant, impermeable gloves. Recommended gloves include

rubber and neoprene. Use of impervious apron and boots are recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:PasteColor:TanOdor:OdorlessOdor threshold:Not available.

**pH**: 10

Vapor pressure: 17.6 mm hg (20 °C (68°F))

Boiling point/range: >= 100 °C (>= 212°F)

Melting point/ range: <= 0 °C (<= 32°F)

Specific gravity: 1.26

Vapor density:

Flash point:

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Not determined

Not available.

Not applicable

Not determined

**Solubility in water:** Disperses in water as a suspension

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Decomposition temperature:

Not determined
60 - 70 %
5,000 - 15,000 cp
Not available.

IDH number: 1224571 Product name: BONDERITE L-CA 193 CASTING LUBRICANT ACHESON known as DAG 193

# 10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 1224571

Thermal decomposition can lead to release of irritating gases and vapors.

Incompatible materials: Acids.

Reactivity: Not available.

Conditions to avoid: Excessive heat. Freezing conditions.

# 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

### Potential Health Effects/Symptoms

Inhalation of vapors or mists of the product may be irritating to the respiratory system. Inhalation: Skin contact:

This product is severely irritating to the skin. Corrosive to the skin. Contact with the skin or

mucous membranes may cause severe irritation and burns. Eye contact:

This product may be severely irritating to the eyes. Contact with this product may cause severe

eye damage.

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Ceramic binder	Oral LD50 (RAT) = 1,100 - 1,600 mg/kg Oral LD50 (RAT) = 1.1 g/kg	Corrosive, Irritant
Mica	None	Lung
Vermiculite	None	Respiratory
Quartz (SiO2)	None	Immune system, Lung, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Ceramic binder	No	No	No
Mica	No	No	No
Vermiculite	No	No	No
Quartz (SiO2)	Known To Be Human Carcinogen.	Group 1	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:**Material, if discarded, is not expected to be a characteristic hazardous waste

under RCRA.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

# 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
None above reporting de minimis

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: John DiCerbo, Sr. Regulatory Affairs Specialist

**Issue date:** 11/04/2014

IDH number: 1224571 Product name: BONDERITE L-CA 193 CASTING LUBRICANT ACHESON known as DAG 193

Page 5 of 6

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Product name: BONDERITE L-CA 193 CASTING LUBRICANT ACHESON known as DAG 193

Page 6 of 6

IDH number: 1224571