

Revision Number: 002.0 Issue date: 11/18/2014

### 1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

**BONDERITE L-CA CG 515 Product name:** 

**DIECASTING LUBRICANT ACHESON** 

known as DELTACAST CG-515

Product type: Lubricant Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way Rocky Hill, Connecticut 06067

**United States** Region:

Contact information:

Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1265669

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

### 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

> MAY CAUSE AN ALLERGIC SKIN REACTION. MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1C
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3



### **Precautionary Statements**

Prevention: Do not breathe vapors, mist, or spray. Wash thoroughly after handling. Use only outdoors or in

a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves, eye protection, and face protection.

Response: IF SWALLOWED: Rinse mouth, Do NOT induce vomiting, If on skin (or hair): Take off

immediately all contaminated clothing. IF INHALED: Remove person to fresh air and keep

comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Immediately call a poison control center or physician. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Storage: Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

IDH number: 1265669 Product name: BONDERITE L-CA CG 515 DIECASTING LUBRICANT ACHESON known as **DELTACAST CG-515** 

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Diiron trioxide	1309-37-1	10 - 30
Sodium silcate	1344-09-8	10 - 30

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

Inhalation: Immediately remove victim to fresh air. If symptoms develop and persist, get

medical attention.

Skin contact: Immediately wash skin thoroughly with soap and water. If symptoms develop

and persist, get medical attention.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

**Ingestion:** Get immediate medical attention.

Symptoms: See Section 11.

# 5. FIRE FIGHTING MEASURES

Extinguishing media: Use media appropriate for surrounding material.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

**Unusual fire or explosion hazards:** This product is an aqueous mixture which will not burn. If evaporated to

dryness, the solid residue may pose a moderate fire hazard.

**Hazardous combustion products:** Thermal decomposition can lead to release of irritating gases and vapors.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage. Do not empty into drains / surface water /

ground water. Do not allow to enter the ground / soil.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal.

#### 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Use only in well-ventilated areas. Avoid breathing vapors or mists of this

product. Do not take internally. For industrial use only.

Storage: For safe storage, store between 5 °C (41°F) and 60 °C (140°F)

Protect from freezing.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Diiron trioxide	5 mg/m3 TWA Respirable fraction.	10 mg/m3 PEL Fume.	None	None
Sodium silcate	None	None	None	None

Engineering controls: Ventilation should effectively remove and prevent buildup of any

vapor/mist/fume/dust generated from the handling of this product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible).

**Skin protection:** Wear impervious gloves for prolonged contact. Gloves should be tested to

determine suitability for prolonged contact. Use of an impervious apron is

recommended.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: viscous, Liquid Color: Red Odor: Odorless Odor threshold: Not available. pH: 11.00 - 13.50 Vapor pressure: 17.0 mm hg Boiling point/range: > 100 °C (> 212°F) Melting point/ range: 0 °C (32°F) 1.87 - 1.97

Specific gravity:

Vapor density:

Flash point:

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Not available.

Not available.

Not available.

Solubility in water: Disperses in water as a suspension

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Decomposition temperature:

Not available.

Not available.

1,000 - 5,000 cp

Not available.

### 10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

**Hazardous reactions:** None under normal processing.

Hazardous decomposition products:

IDH number: 1265669

Thermal decomposition can lead to release of irritating gases and vapors. In case of fire toxic

gases can be released.

Incompatible materials: Strong acids.

Reactivity: Not available.

Conditions to avoid: Freezing conditions.

### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

#### **Potential Health Effects/Symptoms**

**Inhalation:** This product is irritating to the respiratory system.

**Skin contact:** This product is irritating to the skin. Prolonged or repeated contact may worsen irritation. **Eye contact:** This product is irritating to the eyes. Prolonged contact may cause severe irritation or corneal

burns.

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Diiron trioxide	None	Allergen, Cardiac, Central nervous system, Irritant, Kidney, Liver, Lung
Sodium silcate	Oral LD50 (RAT) = 1,100 - 1,600 mg/kg Oral LD50 (RAT) = 1.1 g/kg	Corrosive, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Diiron trioxide	No	No	No
Sodium silcate	No	No	No

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:**Dispose of according to Federal, State and local governmental regulations.

**Hazardous waste number:**Wastes must be tested using methods described in 40 CFR Part 261 to

determine if it meets applicable definitions of hazardous wastes.

# 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

# U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

# Water Transportation (IMO/IMDG)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

IDH number: 1265669 Product name: BONDERITE L-CA CG 515 DIECASTING LUBRICANT ACHESON known as DELTACAST CG-515

# 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: None above reporting de minimis

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

**Canada Regulatory Information** 

IDH number: 1265669

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Jennifer Mckay, Regulatory Affairs Specialist

Issue date: 11/18/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.